

Bic 02

Harbour design 2017

Recessed square downlight with trim. Available in two versions: for plasterboard (without housing) and for brickwork (compulsory housing).


Incasso quadrato con bordo. Disponibile nelle versioni per cartongesso (senza cassaforma), e per muratura (cassaforma obbligatoria).

Quadratische Einbauleuchte mit Rand. Lieferbar in den Versionen für Gipskarton (ohne Gehäuse) und für Mauerwerk (Gehäuse zwingend notwendig).

Luminaire carré encastré avec collerette. Disponible dans les versions pour cloison en placoplâtre (sans boîte d'encastrement) et pour mur de brique (boîte d'encastrement obligatoire).

Empotrable cuadrado con borde. Disponible en las versiones para falso techo (sin cajetín) y para ladrillo (cajetín obligatorio).





For plasterboard. Per cartongesso

| | | | | |
|------|--------|----|---|---|
| IP40 | MC-E=3 | CE | ▽ | ⊕ |
|------|--------|----|---|---|

500m/A LED 6W CRI>90

B02.2 ■ S. □ P = 2,0cm

B02H.2 ■ S. □ P = 1,5cm

With honeycomb. Con frangiluce

| ■ Led color | Nominal lm | Beam spread |
|-------------|------------|-------------|
| 2 = 2700°K | 528 | S = 22° |
| 3 = 3000°K | 552 | |
| 4 = 4000°K | 594 | |

☉ (m-M) Converter

DRV.500.15 (1-1) on/off

DRV.501.50 (1-7) DALI - Push - 1...10V (Remote installation)

DRV.502.20 (1-3) DALI (Remote installation)

DRV.503.20 (1-3) Push - 1...10 (Remote installation)

DRV.504.10 (1-1) IGBT - TRIAC

□ Frame - Struttura


02 ● Black - Nero

06 ○ White - Bianco

C ● Copper - Rame

S ● Brass - Ottone

(m-M) = min. Led unit - Max Led unit



For brickwork. Per laterizio

| | | | | |
|------|--------|----|---|---|
| IP40 | MC-E=3 | CE | ▽ | ⊕ |
|------|--------|----|---|---|

500m/A LED 6W CRI>90

B2M.2 ■ S. □ P = 2,0cm


B2MH.2 ■ S. □ P = 1,5cm

With honeycomb. Con frangiluce

| ■ Led color | Nominal lm | Beam spread |
|-------------|------------|-------------|
| 2 = 2700°K | 528 | S = 22° |
| 3 = 3000°K | 552 | |
| 4 = 4000°K | 594 | |


☉ (m-M) Converter

DRV.500.15 (1-1) on/off



Housing for brickwork. Cassaforma per laterizio

M02.050.01



For plasterboard. Per cartongesso

| | | | | |
|------|--------|----|---|---|
| IP40 | MC-E=3 | CE | ▽ | ⊕ |
|------|--------|----|---|---|

350m/A LED 11W CRI>85 H = 9,2

B02.3 ■ S. □ P = 2,6cm

B02H.3 ■ S. □ P = 2,1cm

With honeycomb. Con frangiluce

| ■ Led color | Nominal lm | Beam spread |
|-------------|------------|-------------|
| 2 = 2700°K | 1195 | S = 22° |
| 3 = 3000°K | 1257 | T = 15° |
| 4 = 4000°K | 1313 | |

☉ (m-M) Converter

DRV.350.1L (1-1) on/off

DRV.350.25 (2-2) on/off

DRV.351.40 (1-3) DALI - Push - 1...10V (Remote installation)

DRV.352.15 (1-1) DALI

DRV.353.15 (1-1) Push - 1...10V

DRV.354.18 (1-1) IGBT - TRIAC

□ Frame - Struttura


02 ● Black - Nero

06 ○ White - Bianco

C ● Copper - Rame

S ● Brass - Ottone

(m-M) = min. Led unit - Max Led unit



For brickwork. Per laterizio

| | | | | |
|------|--------|----|---|---|
| IP40 | MC-E=3 | CE | ▽ | ⊕ |
|------|--------|----|---|---|

350m/A LED 11W CRI>85

B2M.3 ■ S. □ P = 2,6cm

B2MH.3 ■ S. □ P = 2,1cm

With honeycomb. Con frangiluce

| ■ Led color | Nominal lm | Beam spread |
|-------------|------------|-------------|
| 2 = 2700°K | 1195 | S = 22° |
| 3 = 3000°K | 1257 | T = 15° |
| 4 = 4000°K | 1313 | |

☉ (m-M) Converter


DRV.350.1L (1-1) on/off

DRV.350.25 (2-2) on/off

DRV.352.15 (1-1) DALI

DRV.353.15 (1-1) Push - 1...10V

DRV.354.18 (1-1) IGBT - TRIAC



Housing for brickwork. Cassaforma per laterizio


M02.080.01



Red/Rosso



Rose/Rosa



Green/Verde



Blue/Blu



Brass/Ottone



Copper/Rame

The colour rendering of these samples is approximate, not being possible to faithfully reproduce by offset printing.

I campioni colore sono solamente indicativi, non essendo possibile la riproduzione fedele a mezzo stampa offset.

Durch den Offset-Druck sind leichte Farbabweichungen der hier gezeigten Muster möglich.

Les échantillons de couleurs sont indicatifs, l'impression papier ne permettant pas une reproduction fidèle.

Las muestras de color son sólo indicativas, no siendo posible una reproducción fiel mediante impresión en papel.

Ⓐ Alimentatore incluso
control gear included
Vorschaltgerät mitgeliefert
platine d'alimentation fournie
alimentador incluido

Ⓒ Converter incluso
Converter included
Konverter mitgeliefert
Convertisseur fourni
Convertidor incluido

Ⓓ Lampadina inclusa
including bulb
Leuchtmittel inklusiv
ampoule comprise
bombilla incluida

Ⓙ Trasformatore incluso
transformer included
Trafo mitgeliefert
transformateur fournie
transformador incluido

Ⓐ Alimentatore non incluso
control gear not included
Vorschaltgerät nicht mitgeliefert
platine d'alimentation non fournie
alimentador excluido

Ⓒ Converter non incluso
Converter not included
Konverter nicht mitgeliefert
Convertisseur non fourni
Convertidor excluido

Ⓓ Lampadina non inclusa
Bulb not included
Leuchtmittel nicht mitgeliefert
Ampoule non fourni
Bombilla excluida

Ⓙ Trasformatore non incluso
transformer not included
Trafo nicht mitgeliefert
transformateur non fournie
transformador excluido

IP identification

IP2X protezione contro corpi estranei ≥ 12mm
protection against solid objects ≥ 12mm
Schutz gegen Fremdkörpern ≥ 12 mm
protection contre des corps étrangers ≥ 12mm
protegido contra objetos extraños ≥ 12mm

IP4X protection against solid objects ≥ 1mm
protezione contro corpi estranei ≥ 1mm
Schutz gegen Fremdkörpern ≥ 1mm
protection contre des corps étrangers ≥ 1mm
protegido contra objetos extraños ≥ 1mm

IPX0 nessuna protezione
no protection
kein Schutz
non protégé
sin protección

“Creativity is inventing, experimenting, growing, taking risks, breaking rules, making mistakes, and having fun.”

Mary L. Cook